



# TRISEP® ACM1

## High Rejection

## Brackish Water RO Elements

The TRISEP® ACM series of brackish water RO membranes is versatile enough to be used in a wide variety of water purification and process applications. ACM1 membrane elements offer very high solute rejection in a variety of strong and durable spiral-wound element designs that may be customized to meet customer requirements.

### MEMBRANE CHARACTERISTICS

<b>Membrane</b>	ACM1
<b>Stabilized Salt Rejection (%)</b>	99.5
<b>Minimum Salt Rejection (%)</b>	99.0

### DESIGN INFORMATION

Model	Part Number	Permeate Flow m <sup>3</sup> /day (GPD) <sup>a</sup>	Membrane Area m <sup>2</sup> (ft <sup>2</sup> )	Feed Spacer Thickness (mil) <sup>b</sup>
<b>TRISEP® 2540-ACM1-TSF</b>	164000251	2.1 (550)	2.4 (26)	31
<b>TRISEP® 4040-ACM1-TSF</b>	161020442	7.2 (1,900)	7.9 (85)	31

<sup>a</sup> Test conditions: 2,000 ppm NaCl, 15.5 bar (225 psi), 25°C (77°F), 15% recovery, pH 8.0, 30 minutes operation. Flow rates will be no more than 15% below the values shown. Product specifications may change without notice as design revisions occur.

<sup>b</sup> All models on this sheet have fiberglass outer wrap. All 47 mil feed spacers are parallel; all other models have diamond shaped feed spacers.

### OPERATING PARAMETERS

<b>Maximum Operating Pressure</b>	41 bar (600 psi)
<b>Maximum Operating Temperature</b>	45°C (113°F)
<b>Cleaning pH Range<sup>1</sup></b>	1.0 - 12.0
<b>Chlorine Tolerance<sup>2</sup></b>	< 0.1 ppm
<b>Maximum Pressure Drop</b>	1 bar (15 psi) per element; 4 bar (60 psi) per housing
<b>Maximum SDI<sub>15</sub></b>	5.0
<b>Maximum Turbidity</b>	1 NTU

<sup>1</sup> Refer to temperature and pH limits in Membrane Cleaning Guide - Water Application Elements (TSG-C-001).

<sup>2</sup> Pretreatment is recommended for the removal of free chlorine and other oxidizing agents to prevent damage to membranes. Oxidizing agents, such as free chlorine, in contact with polyamide membranes may result in shortened operating life or membrane failure. Such oxidation damage is excluded from warranty. Refer to Membrane Operating Guide - Recommendations for Water Purification (TSG-O-012).


**PHYSICAL DIMENSIONS**

Model	Element Weight kg (lb) <sup>c</sup>	Dim. A mm (inches)	Dim. B mm (inches)	Dim. C <sup>d</sup> mm (inches)	Permeate Tube <sup>e</sup>
TRISEP® 2540-ACM1-TSF	3 (7)	1,016 (40.0)	64 (2.5)	19.1 (0.75)	Male
TRISEP® 4040-ACM1-TSF	4 (9)	1,016 (40.0)	99 (3.9)	19.1 (0.75)	Male

c Shipping weight is dependent on packaging material and quantity shipped.

d Dimension "C" is the Outer Diameter.

e Male elements have a protruding permeate tube, indicated as "D" in the diagram. Dimension "D" is 25.4 mm (1.0 in).



**IMPORTANT INFORMATION**

**Start-up:** MANN+HUMMEL Water & Fluid Solutions recommends flushing elements for 30 minutes at low pressure and discarding permeate during the flush prior to operation. For a more detailed start-up procedure, please see Element Start-Up Guide – System Start-Up (TSG-O-005).

**Cleaning:** TRISEP® membrane elements must be cleaned periodically to ensure proper operation and to prevent membrane damage. Please see Membrane Cleaning Guide – Water Application Elements (TSG-C-001).

**Storage:** TRISEP membrane elements must be stored appropriately to ensure proper operation and to prevent membrane damage. Please see Element Storage Guides (TSG-O-009 & TSG-O-010).

**CUSTOMIZABLE SPECIALTY ELEMENTS**

MANN+HUMMEL Water & Fluid Solutions offers a full range of membranes and element designs for challenging water and process applications. Technologies include low-fouling RO, submerged UF, continuous high temperature, ultra-high pressure, unique sanitary designs and more. Contact us to customize a product that satisfies your specific requirements.

**Contact**

**Europe**

Germany: +49 611 962 6001  
Italy: +39 0721 1796201  
info@microdyn-nadir.com

**Americas**

USA: +1 805 964 8003  
sales.mnus@microdyn-nadir.com

**Asia**

Singapore: +65 6457 7533  
China: +86 10 8413 9860  
waterchina@mann-hummel.com