

NADIR® UP150 P

Ultrafiltration Membrane

NADIR® UP150 membrane is a polyethersulfone (PES) ultrafiltration membrane with a nominal molecular weight cut-off (M.W.C.O.) of 150,000 Daltons. UP150 membrane is commonly used in the removal of macromolecules or concentration of large organic solutes in both water and process applications, and can be used for membrane bioreactor (MBR) applications. UP150 membrane sheet is available in dry flat sheet rolls and is FDA compliant.

MEMBRANE CHARACTERISTICS

Membrane Chemistry	Backing Material	Nominal M.W.C.O. (Da)
Polyethersulfone (PES)	Polypropylene	150,000

Permeability LMH/bar (GFD/psi) ^a	Thickness (µm)	pH Range	Chlorine Tolerance ^b
≥ 285 (≥ 11.6)	210 – 250	0.0 – 14.0	500,000 ppm·hours

^a Test conditions: Clean water, 2 bar (29 psi), 20°C (68°F), crossflow operation. Membrane specifications may change without notice as design revisions occur.
^b pH must be between 10 – 11 during chlorine cleaning.

IMPORTANT INFORMATION

Standard Sizes: NADIR flat sheet membrane is available in an A4 sample size of 210 mm x 297 mm (8.27 in x 11.69 in) and in a nominal roll size of 150 m x 1016 mm (492 ft x 40.0 in). Custom lengths may be available on request.

Initial Flush: MANN+HUMMEL Water & Fluid Solutions recommends flushing membrane for 30 minutes and discarding permeate during the flush prior to operation.

Storage: Membrane shipped dry should be stored away from direct sunlight in a cool, dry place. Please see Membrane Storage Guide – Flat Sheet Membrane (TSG-O-011).

Contact

Europe

Germany: +49 611 962 6001
 Italy: +39 0721 1796201
 info@microdyn-nadir.com

Americas

USA: +1 805 964 8003
 sales.mnus@microdyn-nadir.com

Asia

Singapore: +65 6457 7533
 China: +86 10 8413 9860
 waterchina@mann-hummel.com